



AlfaNova HP 27

Fusion-bonded plate heat exchanger

General information

AlfaNova is a plate heat exchanger made of 100% stainless steel. It is based on Alfa Laval's revolutionary technology, AlfaFusion, the art of joining stainless steel components together.

AlfaNova heat exchangers are well suited in applications which put high demand on cleanliness, applications where ammonia is used or applications where copper or nickel contamination is not accepted. Its high resistance to corrosion makes it both hygienic and environmental friendly.

It is extremely compact compared to its capacity to withstand great strains in demanding heat transfer applications.

Applications

Within refrigeration:

- Oil cooling
- Condensing
- Evaporating
- Economizing
- Desuperheating
- Absorption systems

Other main applications:

- Domestic hot water heating
- Process cooling
- Hydraulic oil cooling
- Laser cooling
- Hygienic/sanitary application
- Water/water cooling & heating

Working principles

The heating surface consists of thin corrugated metal plates stacked on top of each other. Channels are formed between the plates and corner ports are arranged so that the two media flow through alternate channels, always in countercurrent flow. The media are kept in the unit by a bonded seal around the edge of the plates. The contact points of the plates are also bonded to withstand the pressure of the media handled.

Standard design

The plate pack is covered by cover plates. Connections are located in the front or rear cover plate. The channel plates are corrugated to improve heat transfer design.




Particulars required for quotation

To enable Alfa Laval's representative to make a specific quotation, enquiries should be accompanied by the following particulars:

- Flow rates or heat load required
- Temperature program
- Physical properties of liquids in question
- Desired working pressure
- Maximum permitted pressure drop

Examples of connections




External threaded

Internal threaded

Soldering


Welding

AlfaNova HP 27 – PED approval pressure/temperature graph 1)




1) Min. temperature -10°C (14°F) with connection tube made of carbon steel.

AlfaNova HP 27 – ASME approval pressure/temperature graph 2)



2) Min. temperature -49°F (45°C) with connection tube made of carbon steel.

AlfaNova HP 27 – CRN approval pressure/temperature graph



Standard data

Min. working temperature	see graph
Max. working temperature	see graph
Min. working pressure	vacuum
Max. working pressure	see graph
Volume per channel, litres (ga)	0.05 (0.013)
Max. particle size mm (inch)	1.2 (0.05)
Max. flowrate* m³/h (gpm)	14 (61.6)
Min. nbr of plates	6
Max. nbr of plates	100

*) Water at 5 m/s (16.4 ft/s) (connection velocity)


Standard dimensions *

A measure mm	= 13 + (2.42 * n) ±4.5 mm
A measure inch	= 0.51 + (0.1 * n) ±0.18 inch
Weight kg	= 1.5 + (0.13 * n)
Weight lb	= 3.31 + (0.29 * n)

(n = number of plates)

Standard materials

Cover plates	Stainless steel
Connections	Stainless steel
Plates	Stainless steel
AlfaFusion filler	Stainless steel



For exact values please contact your local Alfa Laval representative.

How to contact Alfa Laval

Up-to-date AlfaLaval contact details for all countries are always available on our website on www.alfalaval.com